


# meeting pod xxl

PRODUCT SPECIFICATION SHEET

This document contains technical information about the MEETING POD XXL



# MODULAR DESIGN MADE WITH SUSTAINABLE MATERIALS, MANUFACTURED LOCALLY FOR A CIRCULAR ECONOMY

In today's interconnected world, where the boundaries between our personal and professional lives are seamlessly merging and constant internet connectivity drives perpetual communication, maintaining privacy and tranquillity has become a crucial aspect of our daily routine an imperative design consideration in today's open and collaborative working and learning environments.

Introducing the MEETING POD XXL, a noise-isolating oasis.

The MEETING POD XXL offers various integration possibilities for its side- and back panels. It provides options for an integrated tabletop that can be elevated with stools for a or set at a lower position with visitor chairs for a grounded experience. Furthermore, on the rear side, a tabletop can be seamlessly incorporated, available in elevated configurations with five to eight stools for dynamic discussions or in a low position with visitor chairs on both sides, perfect for extended meetings involving ten to twelve individuals.

The MEETING POD XXL effortlessly blends into any preexisting or new space, arriving fully equipped with a motion-sensor-driven fresh air ventilation system, an automated LED lighting system, a primary power connection (230V), and multiple integrated multifunctional power sockets. (Includes 2 wooden crates, 4 ventilators, accommodates 10-12 persons, different long meeting table option available).

Due to the large size of the MEETING POD XXL various interiors can be created. A second door at the back side of the pod is possible when people need to access the pod from both directions. The door can be placed in the middle or at the left- or right side of the facade.

Design by Ecolution

---

## CONTENT

Technical data	page 3
Dimensions	page 4
Ventilation	page 5
Electricity & cable management	page 5
Interior & exterior furniture options	page 6
Fabrics & finishes	page 7-8
Acoustic performance data	page 9
Modular range	page 10

---

## CERTIFICATIONS



# TECHNICAL DATE

## MEETING POD XXL

---



### Users

8 to maximum 10 people



### Weight

1103 kg | 2432 lbs



### Installation

10 hours, including unboxing at spot  
Two installers required  
Cordless screwdriver and leveler required



### Outside dimensions

Depth: 2250 mm  
Height: 2333 mm  
With: 4227 mm



### Power:

Mains supply: 230V AC 50-60Hz, max 16A  
Cable connection: GST18  
Stand-by consumption: 2,1 W  
Consumption LED lights (4x) in total: 20 W  
Consumption ventilator (4x) in total: 23,04 W  
Infrared motion sensor time delay: 10 sec-7 min.



### Lighting unit:

Power usage in total: 4x 5 W = 20 W  
Input: 230V AC 50-60 Hz  
Lumen output in total: 900 lumen  
Color Temperature: 2700 K  
Lifespan: +/- 15.000 hours  
Fitting: GU10



### Ventilation unit:

Power usage: 5,76W (4x)  
Input: 12V DC  
Airflow rate when occupied: 235 m3/h  
Ventilators switched of automatically after  
7 minutes without occupancy  
DB per ventilator during occupancy: 5 dB(A)



### Packaging

Knockdown wooden crate  
Dimensions 2390mm / 800mm / 1750mm  
Material planed Pine wood & MDF board  
Required amount of boxes = 2  
Credit for each box when returned  
Optional sofa's and table tops packed separately



### Interior & exterior options

Exterior: shelf (possible in high and low position), LCD-screen panel, magnetic whiteboard  
Interior: side table, shelf, meeting table (all possible in high and low position), LCD-screen panel, magnetic whiteboard, sofa's



### Fabrics and finishes

Interior: upholstered eco-fabric-, eco-felt- or laminated acoustic wood panels  
Exterior: upholstered eco-fabric-, eco-felt- or laminated panels




### Materials

Panels made of 100% recycled wood and panels made of recycled paper and organic waste  
Frame made of powder coated RAL9005 aluminum extrusion profiles and sheet metal  
Acoustic filling made of 100% recycled jeans  
Safety glass panels 5 mm + 5 mm / 0.2 in + 0.2 in  
Insulation material made of 100% recycled textile  
Upholstery made of 50% - 100% recycled textile  
EPDM rubber u-profile for windows and door  
EPDM rubber soundblock profile for door frame

# DIMENSIONS


## MEETING POD XXL




## INTERIOR OPTIONS



MEETING POD XXL with stools and low table.  
Table top 1000/800mm x 2900mm



MEETING POD XXL with stools and high table.  
Table top 700mm x 2900mm



## VENTILATION



ventilation slots



ventilators


Input fresh air: Perforated floor plinths with internal acoustic labyrinth.  
Output air: 2x ventilators integrated in roof.

Airflow rate when occupied: 235 m<sup>3</sup>/h

## LIGHTING



LED-Light



sensor

Directional LED-lights integrated in ceiling: 2x 5 W = 10 W  
Lumen output in total: 900 lumen  
Color Temperature: 2700 K  
Activation: By infrared motion detection integrated in ceiling  
Lifespan LED bulbs: +/- 15.000 hours  
Fitting: GU10

## POWER CONNECTION

The pods can be connected to the network of building from each side of the pod 5cm above the floor or from the roof if preferable. Pods with a mid-panel integrated at the back have an extra option using a 60mm diameter grommet placed 3cm above the floor in the middle. Because the panels at the outside and inside of the pod can be removed, a cable channel inside the wall is accessible and cables can be guided in any direction.

All pods will be delivered with a GST18 power block with four gangs and two five meter GST18 cables to connect the pod with power sockets to the building.



power cables  
with GST18 plug



cable splitter  
for connecting



GST18 power block  
integrated in ceiling tray

## INTEGRATED POWERSOCKET OPTIONS



### POWER SOCKET STANDARD

- 230 volt RA
- including 200mm cable GST18
- 68mm diameter



### UTP Cat6 2x

- Two UTP ports included
- No cables included for ports at the backside
- 68mm diameter



### USB SPEED CHARGING

- 2x USB port include
- including 200mm cable GST18
- 68mm diameter



### Cat6 UTP + 1x HDMI

- 1x UTP Cat6 port included
- 1x HDMI port included
- 68mm diameter

# OPTIONAL

---

## SOFA



Sofa with removable covers  
1650mm x 665mm x 824mm  
Seating height 460mm

Available in different eco-fabrics.

---

## MEETING TABLE



Table top with column leg (RAL9005).  
In high position (1050mm) or low position (750mm)  
800/1000mm x 2900mm , 40mm thick.

Available in different colours, dimensions and positions.

---

## SIDE TABLE



Side table in the wall at the left- or right side of the pod.  
In high position (1050mm) from floor or low position (750 mm).  
Dimensions 500mm x 2140mm

Available in different colours.

---

## SHELF



Shelf integrated in the wall at the left- or right side of the pod.  
In high position (1050mm) from floor or low position (750 mm).  
Dimensions 250mm x 2140mm

Available in different colours.

---

## LCD-SCREEN PANEL



LCD-screen panel, available for inside or  
integrated at the outside of the pods.  
Dimensions 2140mm x 780mm

---

## MAGNETIC WHITE BOARD



Magnetic whiteboard available for inside  
or integrated at the outside of the pods.  
Dimensions 2140mm x 780mm



# FABRICS

## ECO-FABRIC SOTO



42% LESS ENERGY



52% LESS WATER



46% LESS CO2



60% WASTE MATERIAL

Price category 1, in various colors  
Composition: 100% recycled PET (plastic bottles waste)  
Weight: 600 g/m2 | 17.64 oz/yd2  
Abrasion resistance: 100.000 Martindale  
Flammability: EN 1021 1-2

## ECO-FABRIC REBO



59% LESS ENERGY



74% LESS WATER



35% LESS CO2



96% WASTE MATERIAL

Price category 1, in various colors  
Composition: 96% recycled PET, 4% NY  
Weight: 590 g/m2 | 17.36 oz/yd2  
Abrasion resistance: 90.000 Martindale  
Flammability: BS 5852

## ECO-FABRIC WOOLY



82% LESS ENERGY



31% LESS WATER




92% LESS CO2



70% WASTE MATERIAL

Price category 2, in various colors  
Composition: 70% Wool recycled / 25% PA recycled / 5% OF  
Weight: 600 g/m2 | 17.64 oz/yd2  
Abrasion resistance: 100.000 Martindale  
Flammability: EN 1021 1-2

## ECO-FABRIC ORGANI



64% LESS ENERGY



22% LESS WATER



89% LESS CO2



50% WASTE MATERIAL

Price category 2, in various colors  
Composition: 50% Wool recycled / 20% PA recycled / 30% LI  
Weight: 550 g/m2 | 16.23 oz/yd2  
Abrasion resistance: 100.000 Martindale  
Flammability: BS 5852-part 1 / EN 1021 1-2


## ECO-FABRIC BLAZER



100% BIO DEGRADABLE

Price category 4, in various colors  
Composition: 100% Virgin Wool  
Weight: 460 g/m2 | 13.55 oz/yd2  
Abrasion resistance: 50.000 Martindale  
Flammability: EN 1021 1-2

## ECO-FABRIC MAIN LINE FLAX



100% BIO DEGRADABLE

Price category 3, in various colors  
Composition: 70% Virgin Wool, 30% flax  
Weight: 437 g/m2 | 12.88 oz/yd2  
Abrasion resistance: 50.000 Martindale  
Flammability: EN 1021 1-2

## ECO-FELT



14% LESS ENERGY



98% LESS WATER



89% LESS CO2



98% WASTE MATERIAL

Price category 2, in various colors  
Composition: 100% recycled textile from different origin.  
Weight: 450 g/m2 | 13.29 oz/yd2  
Abrasion resistance: the felt is not suitable for upholstery of seats  
Flammability: EN 1101 1-2 standard.

# FINISHES

---

## LAMINATED PANELS OUTSIDE




light oak




natural oak



fumed oak




black oak



black mat




brushed gold



brushed aluminum



brushed bronze



brushed metal blue




moss grey



slate grey



wool beige



brown weave

---

## LAMINATED WOODGRAIN ECO PANELS INSIDE



light oak



natural oak



fumed oak



black oak

---

## TABLE & SHELF FINISHES RECYCLED




light oak




natural oak




fumed oak



black oak



black mat




white



# ACOUSTICS



- A** automatic drop-seal integrated in top and bottom of the door
- B** gaps around the door closed with rubber profiles in door frame
- C** sound absorbing labyrinth inside the floor plinths and between ceiling and roof panels
- D** double layered 10,7mm thick glass panels with acoustic layer in between
- E** 110mm thick sound absorbing panels at both sides and at ceiling
- F** 50-shore rubber soft band underneath the floorplinths for different floor surfaces



## ACOUSTICS

Speech level insertion loss  $D_{s,A}$  is 30 dB (measured according to ISO 23351-1), Class category A for the Work Pod (which is of identical build with different geometries). Test report available upon request.

# COLLECTION PODS

---



PHONE POD



FLEX POD



DUO POD



WORK POD



WORK POD LARGE



WORK POD XL



WORK POD XXL



MEETING POD



MEETING POD LARGE



MEETING POD XL



MEETING POD XXL